SafeSealWrap



SAFE SEAL WRAP

# Cable Ties

Safe Seal Wrap's Cable Ties are the perfect solution for securely fastening debris netting to scaffolding structures. Designed with reliability and efficiency in mind, these cable ties are specifically made with UVI to withstand the demands of scaffold environments.

The cable ties are designed to hold debris netting onto the scaffolding. The strong 50 lb tested strength keep a strong hold during high wind events, and the UV inhibitors ensure longevity in the field when fighting UV rays.

**50 LB RATING | UV RESISTANT | 11" LENGTH**

| | |
|---|---|
| MATERIAL: | Virgin Polyethylene |
| COLOR: | Black |
| WIDTH: | 5/16" (8mm) |
| LENGTH: | 11" (280mm) |
| TEMPERATURE RANGE: | -40°C to 85°C |

## Precautions:

Cable ties should be installed with care to avoid over-tightening, which can weaken the tie or damage the material being secured. Always inspect for signs of wear, fatigue, or UV degradation during long-term use. Not designed for load-bearing or lifting applications.

## Applications:

Ideal for fastening debris netting and other lightweight materials to scaffolding, Safe Seal's UV-resistant cable ties offer a secure, weather-resistant hold. With a 50 lb rating, they are suitable for use on construction sites and other exposed environments where durability and reliability are essential.

| PRODUCT CODE | COLOUR | SIZE | PIECES |
|---|---|---|---|
| SSD-CT-11-BLK | Black | 11" | 100 PCS/Bag |
| SSD-CT-11-BLK-CS | Black | 11" | 10,000 PCS/Case |